



Simplex Manufacturing dba Simplex Aerospace  
13340 NE Whitaker Way Portland, OR 97230  
mail@simplexmfg.com www.simplex.aero  
Main Phone (503) 257-3511 Fax (503) 257-8556



# Simplex Model 308 Fire Attack System

Bell 407







## Simplex Model 308 Fire Attack System

Bell 407





Simplex Manufacturing dba Simplex Aerospace  
 13340 NE Whitaker Way Portland, OR 97230  
 mail@simplexmfg.com www.simplex.aero  
 Main Phone (503) 257-3511 Fax (503) 257-8556

# Simplex Model 308 ▪ Fire Attack System

Bell 407

Certifications	
FAA STC #SR00769SE	Bell 407
Argentina ANAC #LV-BBP	Bell 407
Mexico DGAC #IA-450/2017	Bell 407

Features & Benefits	Installation Requirements
FAA certified for day/night VFR operations  Installation/removal in 30 minutes	<ul style="list-style-type: none"> <li>• Approved cargo hook mirror</li> <li>• Approved standard high skid gear</li> </ul>

**The Simplex Model 308 FAS can be installed on the Bell 407 with AA or Bell skid gear.**

FAS Details	
Tank Weight	287 lb / 130 kg
System Capacity	245 gal / 927 L
Foam Capacity	7.5 gal / 28 L
Hover Refill Rate	280 GPM / 1060 LPM
Vne (Hover Pump Installed)	120 KIAS
Vne (Hover Pump Removed)	120 KIAS

Simplex Sales	
<b>Michael Finnegan, Director of Product Sales</b> Europe, Russia, Middle East and Asia mfinnegan@simplexmfg.com	<b>Casey Zimmerman, Regional Sales Manager</b> North/Central/South Americas, Africa and Pacific Islands czimmerman@simplexmfg.com

