



Simplex Manufacturing dba Simplex Aerospace  
13340 NE Whitaker Way Portland, OR 97230  
mail@simplexmfg.com www.simplex.aero  
Main Phone (503) 257-3511 Fax (503) 257-8556



## Simplex Model 310 Fire Attack System

Airbus 350 & 355 Series, H125





## Simplex Model 310 Fire Attack System

Airbus 350 & 355 Series, H125





Simplex Manufacturing dba Simplex Aerospace  
 13340 NE Whitaker Way Portland, OR 97230  
 mail@simplexmfgr.com www.simplex.aero  
 Main Phone (503) 257-3511 Fax (503) 257-8556

# Simplex Model 310 ▪ Fire Attack System

Airbus 350 & 355 Series, H125

C e r t i f i c a t i o n s	
FAA STC #SR00684SE	AS-350B, B1, B2, B3, BA, C, D, D1
FAA STC #SR00689SE	AS-355E, F, F1, F2, N
EASA STC #IM.R.S.0078	AS-350B, B1, B2, BA, B3
EASA STC #IM.R.S.0079	AS-355F, F1, F2, N
Mexico DGAC #IA-158/2012	AS-350B, B1, B2, BA, B3, C, D, D1
Brazil ANAC #2016S12-01	AS-350B, B1, B2, BA, B3
China CAAC	Pending
Canada TC	AS-350B, B1, B2, B3, BA, C, D, D1
Canada TC	AS-355E, F, F1, F2, N

F e a t u r e s & B e n e f i t s	I n s t a l l a t i o n R e q u i r e m e n t s
<p>FAA certified for day VFR operations</p> <p>Installation/removal in 30 minutes</p> <p>Available in 3 sizes: 900 L, 1100 L, or 1200 L</p>	<ul style="list-style-type: none"> <li>• Approved cargo hook mirror system</li> <li>• Approved standard high skid gear</li> <li>• Repositioning of the static port in accordance with Simplex Pitot Static Relocation Kit:</li> </ul> <p>Simplex P/N 300-106008-001            FAA STC #SR01289SE</p>

M o d e l 3 1 0 - 0 0 1	
Tank Weight	281 lb / 127 kg
System Capacity	238 gal / 900 L





Simplex Manufacturing dba Simplex Aerospace  
 13340 NE Whitaker Way Portland, OR 97230  
 mail@simplexmf.com www.simplex.aero  
 Main Phone (503) 257-3511 Fax (503) 257-8556

## Simplex Model 310 ▪ Fire Attack System

Airbus 350 & 355 Series, H125

Model 310-002	
Tank Weight	300 lb / 136 kg
System Capacity	291 gal / 1100 L

Model 310-003	
Tank Weight	302 lb / 137 kg
System Capacity	317 gal / 1200 L

FAS Details (All 310 Models)	
Foam Capacity	21.5 gal / 81 L
Hover Refill Rate	315 GPM / 1192 LPM
Vne (Hover Pump Installed)	120 KIAS
Vne (Hover Pump Removed)	120 KIAS

Simplex Sales	
<b>Michael Finnegan, Director of Product Sales</b> Europe, Russia, Middle East and Asia mfinnegan@simplexmf.com	<b>Casey Zimmerman, Regional Sales Manager</b> North/Central/South Americas, Africa and Pacific Islands czimmerman@simplexmf.com

