



Simplex Manufacturing dba Simplex Aerospace
13340 NE Whitaker Way Portland, OR 97230
mail@simplexmfg.com www.simplex.aero
Main Phone (503) 257-3511 Fax (503) 257-8556

Simplex Model 5200 Spray System

Hughes 269 Series





Simplex Manufacturing dba Simplex Aerospace
13340 NE Whitaker Way Portland, OR 97230
mail@simplexmfg.com www.simplex.aero
Main Phone (503) 257-3511 Fax (503) 257-8556



Simplex Model 5200 Spray System

Hughes 269 Series





Simplex Manufacturing dba Simplex Aerospace
 13340 NE Whitaker Way Portland, OR 97230
 mail@simplexmf.com www.simplex.aero
 Main Phone (503) 257-3511 Fax (503) 257-8556

Simplex Model 5200 ▪ Spray System

Hughes 269 Series

Certifications	
FAA STC #SR02276SE	H269 Series
Canada TC #4H12	H269 Series
Australia CAA Validation	H269 Series

Features & Benefits	
<p>Installation/removal in 30 minutes</p> <p>Flow controller allows operator to adjust chemical output.</p>	<p>Aft-mounted booms.</p> <p>Aerodynamic design results in low drag.</p> <p>Safety features include emergency jettison dump doors and pump stop controls.</p>

Spray System Details	
Average Tank Weight	120 lb / 54 kg
Capacity	90 gal / 341 L
Boom Span	27 ft / 8 m
Estimated Swath Width	45-55 ft / 14-17 m
Nozzle Ports	52 (¼" NPT)
Vne	55 MPH / 47.79 KIAS

Installation Requirements	Electrical Requirements
<ul style="list-style-type: none"> Approved standard high skid gear 	<p>Current: 90 Amps</p> <p>Voltage: 28 VDC</p>

Simplex Sales	
<p>Michael Finnegan, Director of Product Sales Europe, Russia, Middle East and Asia mfinnegan@simplexmf.com</p>	<p>Casey Zimmerman, Regional Sales Manager North/Central/South Americas, Africa and Pacific Islands czimmerman@simplexmf.com</p>

